



# OFFSHORE PADDLE

## USER GUIDE

### 2021







# CONTENTS

- Welcome to the Offshore Paddle family
- Getting to know your Adventure Board II
- How to inflate your Adventure Board II
- How to ride your Adventure Board II
- How to deflate your Adventure Board II
- Warranty and safety





# WELCOME TO THE OFFSHORE PADDLE FAMILY

We are thrilled to welcome you to our  
Offshore Paddle family !

Here at Offshore Paddle, we take pride  
in our boards and we hope that you will  
love them as much as we do.

This guide is designed to introduce you  
to your new Adventure Board II and to  
get you out on the water as quickly and  
as safely as possible.



# GETTING TO KNOW YOUR ADVENTURE BOARD II

Your Offshore Paddle bundle includes:

- Offshore Paddle Adventure Board II
  - Size: 10' 6" x 32"
  - Thickness: 6"
  - Air Chambers: 1
  - Net Weight: 8.9 kg
  - Max Payload: < 150 kg
  - Maximum Pressure: 15 psi
  - Advised pressure: 15 psi
- 2pc adjustable aluminium SUP paddle
- Dual action pump with gauge
- Removable centre fin
- Repair kit
- Leash
- Rucksack





# ADVENTURE BOARD II

- |                          |                           |                         |
|--------------------------|---------------------------|-------------------------|
| <b>1</b> - Valve         | <b>5</b> - Leash ring     | <b>9</b> - Paddle       |
| <b>2</b> - Handle        | <b>6</b> - Leash          | <b>10</b> - Pump        |
| <b>3</b> - Luggage strap | <b>7</b> - Detachable fin | <b>11</b> - Rucksack    |
| <b>4</b> - Traction pads | <b>8</b> - Fin slot       | <b>12</b> - Repair kit. |







# HOW TO INFLATE YOUR ADVENTURE BOARD II







1. Lay your Adventure Board II on a flat surface - make sure that you avoid any sharp objects.
2. Attach the pump hose to the top of the pump (near to the gauge).
3. Remove the valve cover.
4. Ensure that the non-return valve is in its outward position. To do this, press the valve either once or twice.
5. Connect the pump hose to the board by inserting it into the valve and turning clockwise.
6. Once inserted, inflate the board to 15psi using your dual action pump. Once pumping becomes difficult, remove the stopper at the top of the pump (near the gauge) to switch to single action.
7. Once inflated, disengage the pump hose by turning anticlockwise.
8. Replace the valve cover and ensure that it is watertight.
9. Remove fin protectors, insert the fin into the fin slot, and secure using the attached screw and washer.
10. Attach the leash to the leash ring by threading it through the loop attached to the end of the leash.
11. Construct the paddle by inserting the shaft with the handle into the shaft with the paddle. You can adjust the length of your paddle using the clamp at the top of the paddle. (As a guide, we recommend that you extend your arm above your head with a slight bend at your elbow and extend your paddle to this length).





# HOW TO RIDE YOUR ADVENTURE BOARD II







Paddle boarding is a skill that can sometimes take time to master. If you're a beginner, its a good idea to start by kneeling on your board. This provides more stability and allows you to get used to the water before progressing to a standing position.

For the best results when paddling, you should keep your arms as straight as possible, reaching your paddle to the front of your board and pulling it back using your core muscles.

When you want to turn, you should adopt a low stance, look in the direction that you want to go and paddle on the opposite side of your board to the direction of desired movement. As you become more confident, you can also adjust your weight on the board so that you can achieve a tighter turn, or you can use a reverse sweep stroke by inserting your paddle into the water next to the rear of your board and pulling in the opposite direction to a regular paddle stroke.





# HOW TO DEFLATE YOUR ADVENTURE BOARD II







1. Lay your Adventure Board II on a flat surface and remove the centre fin. Be sure to re-secure the screw and washer to the fin to avoid loss.
2. Remove the valve cover and press the valve button downwards firmly.
3. Allow the board to deflate by applying pressure to the board surface. Roll the board from the nose to the fin in order to deflate.
4. To finish deflating your board, attach the pump hose to the base of the pump and to the valve. Use the pump to remove all air remaining in the paddle board.
5. Once fully deflated, disconnect the pump hose, re-attach the valve cover, replace the fin protectors, and roll the board from nose to fins.
6. Disassemble the paddle by pressing the silver pin and pulling apart.
7. Put the deflated board, centre fin and paddle into the rucksack.





# SAFETY AND WARRANTY







It is your responsibility to ensure your own safety on your Offshore Paddle Board. While paddle boarding is relatively safe activity when compared to other water-sports, we strongly recommend that you carefully read the following safety guidance.

- Always check that your equipment is in good condition and is fully assembled before launching.
- We strongly recommend that you always wear a personal floatation device when out on the water.
- Check the weather forecast, tides and swell and be sure to plan and dress accordingly. Remember that heavy rain can affect river levels and that waves, rips and currents require experience to navigate. Consulting websites such as The Met Office and Magic Seaweed is a good idea prior to departing - be sure to pay particular attention to the direction and the strength of the wind.
- If possible, avoid paddling alone and always take a mobile phone with you in a sealed waterproof bag. If this is not possible, always make sure that someone knows where you are and what time you plan to get back. If you are carrying a phone, it is useful to have the what3words app downloaded to help you describe your location to the emergency services if you do get into trouble. If you are in distress, call 999 and ask for the coastguard.
- When exploring somewhere new, don't be afraid to speak to others out on the water - they may have some local knowledge about tides and currents.
- If possible, avoid offshore winds as they may blow you far out to sea and make it difficult to paddle back to shore.





Your Offshore Paddle Adventure Board II is covered by a 24 month manufacturer warranty.

If your Offshore Paddle Adventure Board II is found to be defective in any way, please contact Offshore Paddle via the email: **[jonny.singh@offshore-paddle.com](mailto:jonny.singh@offshore-paddle.com)**

We regret that the following are limitations of the application of this warranty:

- The product must be stored and cared for correctly.
- The product must not be modified in any way.
- The product must be assembled and disassembled according to pressure recommendations and guidance.
- This warranty does not cover parts that are not provided by Offshore Paddle or a recommended manufacturer.







# A FINAL WORD FROM US

Thank you for your purchase of an Offshore Paddle Adventure Board II, we hope that you love our boards as much as we do !

If you have any questions, feel free to contact us any time via email ([info@offshore-paddle.com](mailto:info@offshore-paddle.com)) or via our instagram ([@offshorepaddle](https://www.instagram.com/offshorepaddle)).

Here at Offshore Paddle HQ we'd love to see photos of you enjoying your new board. Be sure to tag us in your photos on Instagram using the hashtag [#offshorepaddeadventure](https://www.instagram.com/explore/tags/offshorepaddeadventure) .

Happy paddling!

